

## TEXTUREFIX-120

Primer / bonding bridge for texture mortars



(SPAIN GREEN BUILDING COUNCIL)

### DESCRIPTION

TEXTUREFIX-120 is a water-based acrylic and vinyl primer, to be used in construction as a bridge joint between new and old mortar shows good penetration and cohesion capacity due to its particle size and residual tack.

It also improve the conditions for adhesion to the vertical substrate supports, a step that should be taken before applying the covering.

### FEATURES AND APPLICATIONS

- TEXTUREFIX-120 is specially recommended to be used as primer before applying PAVILAND PLUS (horizontal supports), MORCEM TEXTURE (vertical supports) and any stamped, repair, polish, etc... mortars.
- It increases the resistance to flexural cracks, as well as the cohesion and impermeability of the system
- Apply a layer of TEXTUREFIX-120 as a primer on vertical supports. Avoid applying the product on exteriors when there's a risk of rain or frost.

### INSTRUCTIONS FOR USE

#### HORIZONTAL SUPPORTS

- Support should be clean and free from grease, oil, oxide, paint remains and loose or badly adhered pieces.
- Spread the product directly by means of a sprayer, making sure to leave a uniform film, without excessive product accumulation and avoiding overly thick layers.

#### VERTICAL SUPPORTS

- The supports should be clean, dry, and well attached. Without diluting, apply a layer with a brush, roller, or spray gun.

### CAUTIONS AND RECOMMENDATIONS

- Do not apply the product with ambient temperature lower than 5°C or higher than 35°C.
- Do not apply either faced with risk of frost or rain, or with relative humidity over 85%. Nor should it be applied under blazing sun.
- The use of gloves is advisable during its manipulation.
- TEXTUREFIX-120 is not toxic, dangerous or flammable under normal handling conditions. It is not necessary to use special safety measures, the stipulations provided in the Work Risks Prevention Law shall be applied at all times.

### PACKAGING

5 and 25 l bags.

Up to 24 months storage in its original closed package, sheltered from bad weather and humidity, avoiding product exposure to temperatures lower than 5°C or higher than 35°C.

## TEXTUREFIX-120

### NOTE

Instructions of use are given based on our testing and knowledge and do not imply any commitment. Said instructions do not free the user from examining and verifying the product for its correct use. The manufacturer's liability is limited to the value of the used goods. Complaints must be accompanied with the original package to allow proper traceability.

### TECHNICAL DATA

(Statistical data obtained under standard conditions)	
Aspect	Milky liquid
Density 20°C	1,01 ± 0,02 g/cm <sup>3</sup>
Solid content	24,5 ± 0,02%

Rd 227/2006 Cat A/g lim 2007/10:50/30g/l; max. COVs: 20g/l



**SIRIO**  
GROUP

Sirio Group srl

Via D. Corvi 26  
60019 Senigallia (AN) Italy  
Tel. +39 071.65512 Fax. +39 071.7913971  
[www.sirio-group.it](http://www.sirio-group.it) – [info@sirio-group.it](mailto:info@sirio-group.it)